

สวิตช์ลากลอย แบบ 2 ตั้ม PD-76AB

MODEL: PD-76AB

Function:
Automatic level control.
Features:

- (1) Applicable to 1 HP and less power rating pumps for water supply and drainage.
- (2) Additional magnetic contactor is not required.

Installation:

- (1) For water supply, connect A1-A2.
- (2) For drainage, connect B1-B2.

Notes:

- (1) Do not touch with hand. switch

Notes:

- (1) A1 ⊖ —SUPPLY— ⊖ A2
B1 ⊖ —DRAINAGE— ⊖ B2
- (2) Applicable to 1 HP and less power rating pumps.



Sazn (ลูกตุ้มสีขาว) ST-70AB

รหัส FL020 ราคา 300 บาท (ต้องเติมน้ำในลูกตุ้ม)

Sazn (ลูกตุ้มสีเหลือง) PD-76AB

รหัส FL002 ราคา 255 บาท

หมายเหตุ: ต่อผ่านแมกเนติกเท่านั้น

Spec.



สวิตช์ลากลอย น้ำเสีย ST-75 สายยาว 5 เมตร



รหัส FL015 ราคา 2,200 บาท

Electric Current : 5A

Voltage : AC 110/220V, 1/2 HP

Temperature of working : 5-60°C



สำหรับระบบบำบัดน้ำเสีย, ถังบำบัดน้ำเสีย และ ควบคุมระดับของเหลว



TERMINAL IDENTITY

Blue and yellow are for draining,

Brown and yellow are for supplying.






CONNECTION:

1. AC Connection: as Fig 1, Do not connect directly, a relay is required.
2. DC Connection: as Fig 2, a liquid level controller is required.

SUGGESTION:

To prevent unusual liquid level, another set of switch could be installed as alarm, or use an additional water pump for draining. (Installing position needs to be higher)



CONDITIONS:

Locations below should be avoided to prevent malfunction.

1. Around water entrance or huge wave Fig.A
2. Pipes or walls should be avoided in float's working range. Fig.B
3. Avoid tangled cables when multi applying. Fig.C